



| General Purpose 20' x 8' x 8'6" | | Steel | |
|--|-------------|--------------|-----------|
| | | Millimetres | Feet |
| Internal Dimensions | Length | 5,898 | 19'4.2" |
| | Width | 2,352 | 7'8.6" |
| | Height | 2,391 | 7'10" |
| Door Opening | Width | 2,340 | 7'8." |
| | Height | 2,280 | 7'5.8" |
| | | Kilograms | Pounds |
| Weight | Max Gross | 24,000 | 52,910 |
| | Tare | 2,280 | 5,090 |
| | Max Payload | 21,720 | 47,885 |
| | | Cube Metres | Cube Feet |
| Internal Capacity | | 33.2 | 1,171 |

| General Purpose 40' x 8' x 8'6" | | Steel | | Aluminium | |
|--|-------------|--------------|-----------|------------------|-----------|
| | | Millimetres | Feet | Millimetres | Feet |
| Internal Dimensions | Length | 12,040 | 39'5.3" | 12,021 | 39'5.3" |
| | Width | 2,353 | 7'8.5" | 2,335 | 7'8.9" |
| | Height | 2,383 | 7'9.7" | 2,360 | 7'8.9" |
| Door Opening | Width | 2,340 | 7'8" | 2,337 | 7'7.9" |
| | Height | 2,280 | 7'5.8" | 2,271 | 7'5.4" |
| | | Kilograms | Pounds | Kilograms | Pounds |
| Weight | Max Gross | 30,480 | 67,200 | 32,000 | 70,040 |
| | Tare | 3,830 | 8,450 | 3,170 | 6,990 |
| | Max Payload | 26,650 | 58,630 | 28,830 | 63,500 |
| | | Cube Metres | Cube Feet | Cube Metres | Cube Feet |
| Internal Capacity | | 67.7 | 2,390 | 67.7 | 2,380 |



| High Cube 40' x 8' x 9'6" | | Steel | |
|--|-------------|--------------|-----------|
| | | Millimetres | Feet |
| Internal Dimensions | Length | 12,031 | 29'5.6" |
| | Width | 2,352 | 7'8.5" |
| | Height | 2,698 | 8'10" |
| Door Opening | Width | 2,340 | 7'8.1" |
| | Height | 2,585 | 8'5.8" |
| | | Kilograms | Pounds |
| Weight | Max Gross | 30,480 | 67,200 |
| | Tare | 3,980 | 8,775 |
| | Max Payload | 26,060 | 58,425 |
| | | Cube Metres | Cube Feet |
| Internal Capacity | | 76.3 | 2,694 |

| High Cube 45' x 8' x 9'6" | | Steel | | Aluminium | |
|--|-------------|--------------|-----------|------------------|-----------|
| | | Millimetres | Feet | Millimetres | Feet |
| Internal Dimensions | Length | 13,544 | 44'5.2" | 13,583 | 44'6.7" |
| | Width | 2,352 | 7'8.5" | 2,345 | 7'8.3" |
| | Height | 2,698 | 8'10" | 2,687 | 8'9.7" |
| Door Opening | Width | 2,340 | 7'8.1" | 2,343 | 7'8.2" |
| | Height | 2,585 | 8'5.8" | 2,585 | 8'5.8" |
| | | Kilograms | Pounds | Kilograms | Pounds |
| Weight | Max Gross | 30,480 | 67,200 | 30,480 | 67,200 |
| | Tare | 4,800 | 10,580 | 3,980 | 8,780 |
| | Max Payload | 25,680 | 56,614 | 26,500 | 58,420 |
| | | Cube Metres | Cube Feet | Cube Metres | Cube Feet |
| Internal Capacity | | 86 | 3,040 | 85.6 | 3,023 |



| Open Top 40' x 8' x 8'6" | | Steel | |
|---|-------------|--------------|-----------|
| | | Millimetres | Feet |
| Internal Dimensions | Length | 12,021 | 39'5.2" |
| | Width | 2,350 | 7'8.4" |
| | Height | 2,234 | 7'7.7" |
| Door Opening | Width | 2,338 | 7'8" |
| | Height | 2,234 | 7'3.8" |
| | | Kilograms | Pounds |
| Weight | Max Gross | 36,000 | 79,370 |
| | Tare | 4,430 | 9,760 |
| | Max Payload | 31,570 | 69,600 |
| | | Cube Metres | Cube Feet |
| Internal Capacity | | 66.7 | 2.355 |

| Open Top 20' x 8' x 8'6" | | Steel | | Steel | |
|---|-------------|--------------------|------------------|--------------------|------------------|
| | | Millimetres | Feet | Millimetres | Feet |
| Internal Dimensions | Length | 5,902 | 19'4.3" | 5,887 | 19'3.7" |
| | Width | 2,240 | 7'4.1" | 2,350 | 7'7.7" |
| | Height | 2,352 | 7'.8.5" | 2,330 | 7'.7.7" |
| Door Opening | Width | 2,335 | 7'7.9" | 2,338 | 7'8" |
| | Height | 2,240 | 7'4.1" | 2,223 | 7'3.5" |
| | | Kilograms | Pounds | Kilograms | Pounds |
| Weight | Max Gross | 24,000 | 52,910 | 24,000 | 52,910 |
| | Tare | 2,440 | 5,380 | 2,560 | 5,640 |
| | Max Payload | 21,560 | 47,520 | 21,440 | 47,270 |
| | | Cube Metres | Cube Feet | Cube Metres | Cube Feet |
| Internal Capacity | | 32 | 1,133 | 32.2 | 1,138 |



| Flatracks | | | Steel | |
|------------------------|-------------|----------|--------------|-----------|
| 40' x 8' x 8'6" | | | Millimetres | Feet |
| Internal Dimensions | Length | | 12,032 | 39'5.6" |
| | Width | | 2,240 | 7'4.1" |
| | Height | Unfolded | 2,034 | 6'8.1" |
| | | Folded | 570 | 1'10.4" |
| | | | Kilograms | Pounds |
| Weight | Max Gross | | 45,000 | 88,180 |
| | Tare | | 5,530 | 12,190 |
| | Max Payload | | 39,470 | 87,020 |
| | | | Cube Metres | Cube Feet |
| Internal Capacity | | | 54.8 | 1936 |

| Flatracks | | | Steel | |
|------------------------|-------------|----------|--------------|-----------|
| 20' x 8' x 8'6" | | | Millimetres | Feet |
| Internal Dimensions | Length | | 5,727 | 18'9.4" |
| | Width | | 2,240 | 7'4.1" |
| | Height | Unfolded | 2,170 | 7'1.3" |
| | | Folded | 420 | 1'4.6" |
| | | | Kilograms | Pounds |
| Weight | Max Gross | | 30,480 | 66,140 |
| | Tare | | 2,950 | 6,500 |
| | Max Payload | | 26,650 | 60,690 |
| | | | Cube Metres | Cube Feet |
| Internal Capacity | | | 27.9 | 986 |



| Refrigerated 40' x 8' x 9'6" | | | Aluminium | |
|---|-------------|----------|------------------|-----------|
| | | | Millimetres | Feet |
| Internal Dimensions | Length | | 11,569 | 37'11.4" |
| | Width | | 2,294 | 7'6.2" |
| | Height | Norminal | 2,540 | 8'4" |
| | | Usable | 2,440 | 8' |
| Door Opening | Width | | 2,294 | 7'6.2" |
| | Height | | 2,558 | 8'4.7" |
| | | | Kilograms | Pounds |
| Weight | Max Gross | | 30,480 | 67,200 |
| | Tare | | 4,420 | 9,750 |
| | Max Payload | | 26,060 | 57,450 |
| | | | Cube Metres | Cube Feet |
| Internal Capacity | Norminal | | 67.4 | 2,380 |
| | Usable | | 64.8 | 2,289 |

| Refrigerated 20' x 8' x 8'6" | | | Aluminium | |
|---|-------------|----------|------------------|-----------|
| | | | Millimetres | Feet |
| Internal Dimensions | Length | | 5,455 | 17'11" |
| | Width | | 2,294 | 7'6.2" |
| | Height | Norminal | 2,288 | 7'6" |
| | | Usable | 2,188 | 7'2" |
| Door Opening | Width | | 2,268 | 7'5.3" |
| | Height | | 2,215 | 7'3.1" |
| | | | Kilograms | Pounds |
| Weight | Max Gross | | 24,000 | 52,800 |
| | Tare | | 2,950 | 6,503 |
| | Max Payload | | 21,050 | 46,407 |
| | | | Cube Metres | Cube Feet |
| Internal Capacity | Norminal | | 28.6 | 1,010 |
| | Usable | | 27.4 | 967 |

